# CATSE PATCH CABLE UNSHIELDED (BARE COPPER)

# SKU: 092 SERIES

#### Conductor

Size 24AWG Stranded Material Bare Copper

#### **Jacket**

Material PVC, CM Rated Diameter 5.4±0.2mm

Operating Temperature -20°C to 60°C

#### Connectors

RJ45 8P/8C Gold Plated

RoHS Compliant Yes

Insulation Resistance Min. 5000 M $\Omega$  Km Conductor Resistance Max. 9.38  $\Omega/100$ m

### **Approvals**

UL cUL Listed, ETL / 3P Certified ANSI/TIA-568-C.2 Category 5e standards.

Available in Black, Blue, Green, Gray, Orange, Purple, Red, White, Yellow.

Check availability with the Account Manager.

# **DESCRIPTION**

Category-5E Mold-Injection-Snagless Ferrari Boot, Patch Cord, 24 AWG Stranded, PVC Jacket.

## **FEATURES**

- Bare Copper Stranded Conductors
- Unshielded RJ45 Modular Plugs
- 8P8C Gold Plated Pins
- 568B Wiring Color Code
- Designed to exceed ANSI/TIA-568-C.2
   Category 5E and ISO 11801 2nd Edition
   Class D+ standards
- RoHS Compliant, UL







